

2026

✓ RELIABLE

✓ INNOVATIVE

✓ BUILD TO LAST

Chemfit **Leading Solutions in Construction & Industry**

***Chemfit** is a manufacturer of specialty construction chemicals, supplying the building and construction industry as well as industrial manufacturing sectors.*

Our product lines feature high-quality concrete admixtures, specialty mortars, sealants and adhesives, structural strengthening systems, industrial flooring, waterproofing and roofing systems.

1. Chemfit Concrete Production Range

Waterproofing Concrete Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit WaterBlock 1000	Concrete admixture in liquid form acting as high-efficiency plasticizer and waterproofing agent; conforms to ASTM C 494 Type A.	To produce dense structural concrete for water retaining structures such as reservoirs, dams, sewage works, canals, roof slabs.	200 L drums, 1000 L IBC	0.5% by weight of cement
Chemfit HydroBlock WA110	Integral waterproofing admixture for concrete and mortar; conforms to BBA standards.	To block capillaries and pores in concrete and plaster.	5 L, 25 L, 200 L	3 – 9 L per m ³ concrete

Water Reducing & Retarding Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit FlowMax 1000	Powerful concrete plasticizer-retarder for high quality concrete in difficult climatic conditions; conforms to ASTM C-494 Type B & D.	Ready mixed concrete, fair faced concrete, high temperature concreting, long transport distance.	200 L drums, 1000 L IBC	0.3% – 1.0% by cement weight
Chemfit RetardFlow WR200	Concrete plasticizer retarder; conforms to ASTM C494 Type B & D.	Hot weather concreting, long transport, RMC.	200 L, 1000 L IBC	0.3 – 1.0%

High Range Water Reducing Admixtures (Superplasticizers)

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit SpersePro 2000	Superplasticizer and set retarder; conforms to ASTM C-494 Type A & F.	Free flow concrete with low water content and high workability retention.	200 L drums, 1000 L IBC	0.6% – 3.0% by cement weight
Chemfit SpersePlus 2100	Highly effective dual action liquid superplasticizer; conforms to ASTM C-494 Type G.	Free flowing concrete with prolonged slump retention.	200 L drums, 1000 L IBC	0.8% – 2.5% by cement weight

High Range Water Reducing & Retarding Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit RetainFlow SP500	Dual action superplasticizer; ASTM Type G.	Slump retention, hot climates.	200 L, 1000 L IBC	0.8 – 2.5%
Chemfit HeatGuard SP550	Water reducer for hot climate concrete.	Foundations, columns, slabs.	200 L, 1000 L IBC	0.6 – 1.8%

Ultra High Range Water Reducers (PCE Based)

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit UltraFlow PCE700	Third generation polycarboxylate ether superplasticizer.	SCC, high performance concrete.	200 L, 1000 L IBC	0.8 – 1.5%
Chemfit FastCast PCE720	High early strength PCE admixture.	Precast, fast stripping.	200 L, 1000 L IBC	0.5 – 1.5%

Shrinkage Reducing & Special Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit ShrinkGuard SRA100	Shrinkage reducing admixture.	High performance concrete.	25 L, 200 L	0.5 – 2.0%
Chemfit AntiFreeze AF100	Cold weather admixture.	Low temperature concreting.	25 kg, 200 L	~1%

Air Entraining Agent

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit AirMix AE100	Air entraining admixture; ASTM C260.	Roads, dams, mass concrete.	200 L, 1000 L IBC	0.03 – 0.15%

Corrosion Protection Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit CorroShield 5000	Calcium nitrate based corrosion inhibiting admixture.	To inhibit corrosion of steel in reinforced concrete.	200 L drums, 1000 L IBC	10 – 30 L per m ³ concrete
Chemfit CorroShield CI300	Advanced corrosion inhibitor.	Marine & aggressive environments.	200 L, 1000 L IBC	2 – 4%

Specialty Concrete Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit RapidSet HA300	Hardening accelerator; does not contain added chloride.	Early strength structural concrete.	200 L, 1000 L IBC	0.5 – 1.5%

Chemfit FiberPlus FIB12	Synthetic fiber reinforcement; conforms to European Directive 94/62/EC.	To reduce plastic shrinkage cracks; enhances durability in hot climates.	0.6 kg bag	0.6 kg per m ³ concrete
-------------------------	---	--	------------	------------------------------------

Shotcrete Admixtures

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit ShotPro SC200	Polymermodified shotcrete admixture in powder form.	Tunnel linings, structural shells, high-strength gunite.	15 kg bag	4 – 10% by cement weight
Chemfit ShotFast AF SC300	Alkali-free, high performance liquid accelerator for wet & dry spray processes.	Tunnel heading stabilization, rock/slope stabilization, underground linings.	1000 L IBC	3 – 7% by weight of binder

Mould Release Agents

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit MouldEase 7000	Ready-to-use, oil based shutter/mould release agent.	Improves finish of fair faced concrete; increases life of steel, timber, plastic formwork.	200 L drums, 1000 L IBC	25 m ² /L (timber), 50 m ² /L (steel/plastic)
Chemfit ReleaseEco MR200	Concentrated anti-corrosive shutter release agent.	Steel, timber, plastic formwork.	20 L, 200 L	25 – 60 m ² /L

Curing Compounds

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit CCure E15	Paraffin-based curing compound.	Roads, slabs, decks.	20 L, 200 L	5 – 6 m ² /L
Chemfit CCure E7	General curing compound.	Concrete curing.	200 L, 1000 L IBC	5 – 6 m ² /L
Chemfit CCure 90	Resin-based curing compound.	Structural concrete.	20 L, 200 L	~5 m ² /L

2. Chemfit Grouting and Tile Fixing

Cementitious Grouting

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit GroutBase 8000	Cementitious, free flowing, non-shrink precision grout with high ultimate strength; conforms to ASTM C1107 Type C.	Machine foundations, precast columns, concrete anchors, cavities, base plates.	25 kg bag	12.7 – 13.1 L per 25 kg bag
Chemfit Grout High Strength 275	Cementitious, very high strength, non-shrink precision grout that expands in two stages.	Columns in precast construction, concrete anchors, base plates, structural repairs, machine foundations.	25 kg bag	12 L per 25 kg bag

Microconcrete

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit MicroCrete 114	One component, free flowing, high strength, cement based microconcrete for grouting and repair.	To repair deteriorated concrete; ideal for volumes too large for conventional grouts.	40 kg bag	>19 L per 40 kg bag

Epoxy Grouting

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit EpoxyGrout 8100	Solvent free, high strength, pourable, three component epoxy mortar.	Fix bolts, anchors, starter bars; fill cavities in concrete; pile head waterproofing.	32 kg, 64 kg, 128 kg units	Approx 2100 kg/m ³
Chemfit EpoxyGrout MP Slow	3-part, multi purpose, solvent-free, moisture tolerant epoxy grouting system.	Starter bars, anchors, fasteners, tie rods, crane tracks, bridge bearings.	12 kg unit, 144 kg bulk	Approx 2100 kg/m ³
Chemfit EpoxyGrout MP Normal	3-part, multi purpose epoxy grouting system.	Starter bars, anchors, fasteners, tie rods, crane tracks, bridge bearings.	12 kg unit, 144 kg bulk	Approx 2100 kg/m ³
Chemfit EpoxyGrout HE	3-part, high performance, high precision epoxy grouting system.	Starter bars, anchors, fasteners, crane tracks, light rail, bridge bearings.	12 kg unit, 144 kg bulk	Approx 2100 kg/m ³

Epoxy Tile Fixing Adhesives & Grouting

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit EpoxyTile 8400	Thixotropic epoxy resin based tile adhesive.	Fix marble, granite, stone, metal tiles.	34 kg unit	Approx 6 kg/m ² per 3 mm thickness
Chemfit EpoxyCeramic 54	Emulsifiable 2 component epoxy mortar for ceramic tile joints.	Seal joints in ceramic wall/floor coverings subject to chemical/mechanical attack.	5 kg pack (A+B)	Approx 1.7 kg/m ² per mm thickness

3.Chemfit Concrete Repair and Protection Range

Corrosion Inhibitor

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit FerroGard 903	Aqueous impregnation forming a protective monomolecular layer on rebars to prevent corrosion.	To protect concrete rebars from steel corrosion above and below ground.	200 L drum	Approx 0.500 kg/m ² (min 0.3 kg/m ²)

Bonding Agents

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit BondEpoxy 9100	Solvent free, two component bonding agent based on epoxy resin.	Bond new concrete to old concrete, mortar, steel, iron.	5 kg unit	0.3 – 0.8 kg/m ²

Chemfit Bond DV	Synthetic rubber emulsion for cement mortars where good adhesion and water resistance required.	Thin layer patching mortars, renders, screeds, repair mortars, tile fixing.	25 L pail, 200 L drum	See PDS
Chemfit Bond LA	Water resistant bonding agent and mortar improver.	Thin layer patching mortars, renders, screeds, repair mortars, tile fixing.	25 L pail, 200 L drum	See PDS
Chemfit Latex	High performance, water resistant bonding agent and mortar improver; conforms to ASTM C1042 Type II.	Repair, inject, render, coat, waterproof concrete/masonry; bond new concrete to old.	25 L pail, 200 L drum	See PDS

Repair Mortars

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit RepairBase 9200	Multipurpose, cementitious, silica fume and polymer containing, one component repair mortar.	Repair deteriorated concrete, layer thickness 5-30 mm.	25 kg bag	Approx 14 L per 25 kg bag
Chemfit RepairLite 9210	Lightweight, economical, non-sag patching and repair mortar.	Horizontal, vertical, overhead applications, thickness 10-50 mm.	25 kg bag	Approx 14 L per 25 kg bag
Chemfit MonoTop 612	Fiber reinforced, polymer modified repair mortar.	General patch repair of concrete and mortars, thickness 5-30 mm.	25 kg bag	Approx 13 L per 25 kg bag
Chemfit RM600	2-component repair mortar.	Tanks, slabs, structural repair.	20 kg kit	Mix full kit
Chemfit RM700 EP	Epoxy repair mortar (3part).	Heavy-duty repairs, industrial floors.	10 – 30 kg kits	As supplied
Chemfit RapidPlug RP100	Rapid setting plugging mortar.	Active water leak stopping.	5 kg, 25 kg	Add water to stiff consistency

Anchoring Adhesives

Product Name	Description	Uses	Packaging
Chemfit AnchorGrip 9500	Solvent and styrene free, two part polyester anchoring adhesive.	Rebars, threaded rods, bolts, concrete, hollow and solid masonry.	150 mL, 300 mL, 550 mL cartridges
Chemfit AnchorGrip 9510	Epoxy acrylate based, solvent and styrene free, two part anchoring adhesive; conforms to ETAF 001 Part 5 Option 7, ETAG001 TR023, ISO 834.	Rebars, reinforcing steel, threaded rods, bolts, special fastening systems, concrete, solid masonry, steel.	300 mL, 550 mL cartridges
Chemfit AnchorGrip 9520	High performance, two part epoxy resin based, solvent free, thixotropic anchoring adhesive; conforms to ETAG001.	Non-expanding anchors in structural work, mechanical & electrical installation.	250 mL, 400 mL, 1500 mL cartridges
Chemfit AF400	Epoxy anchoring adhesive.	Heavy duty anchoring.	Cartridge / kit

Rigid Bonding Adhesives

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit StructBond 9600	Two part thixotropic, moisture tolerant, solvent free structural adhesive and repair mortar.	Bond concrete, metal, masonry; repair cracks; anchor rebars.	1.2 kg & 6 kg packs	1.9 kg/m ² per mm thickness
Chemfit StructBond 30	Solvent-free, thixotropic, two part structural adhesive.	Bond structural reinforcement, particularly in structural strengthening works.	6 kg pack	See PDS
Chemfit Impreg 300	2-part, solvent free epoxy based impregnating resin.	Bond high density fabrics to concrete, steel, masonry.	10 kg pail	0.4 – 1.0 kg/m ²

4. Chemfit Rigid Bonding & Structural Strengthening

Fabric Wrapping Systems

Product Name	Description	Uses	Dosage/Yield/ Coverage
Chemfit CarboWrap 9900	Unidirectional woven carbon fiber fabric for dry application process.	Strengthen concrete, brickwork, timber under flexural and shear load.	50 m x 300/600 mm rolls
Chemfit GlassWrap 430G	Unidirectional woven glass fiber fabric for dry application process.	Strengthen reinforced concrete structures, brickwork, timber under flexural and shear load.	50 m x 600 mm rolls

5. Waterproofing and Roofing

Quick Setting Agents

Product Name	Description	Uses	Packaging
Chemfit QuickPlug 1100	Cement based rapid setting plug mortar.	Stop and seal water leakages.	5 kg pail
Chemfit RapidSet 4A	Quick setting additive (15-45 seconds).	To preliminary seal wet surfaces prior to final waterproofing system application.	5 kg, 20 kg container

Waterproofing Additive Agents

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit PROOF WP100	Powder integral waterproofer for mortar and concrete.	To waterproof cement/sand mortars, screeds, renders for walls, facades, floor toppings, hot climates	25kg bag	2% by weight of cement

Chemfit PROOF WP101	Powder integral waterproofer for mortar and concrete.	Waterproof cement/sand mortars, screeds, renders.	25 kg bag	2% by weight of cement
---------------------------	---	---	-----------	---------------------------

Cementitious Waterproofing Coatings

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit WaterSeal 500	Cement based, polymer modified, two component waterproofing slurry.	Water and sewage works, basements, retaining walls, irrigation channels.	25 kg set	2.0 – 4.0 kg/m ² per coat
Chemfit Seal 105	Cement based, polymer modified, 2-component multipurpose waterproofing slurry.	Water and sewage works, basements, retaining walls, sea walls, irrigation channels.	25 kg set	2.0 – 4.0 kg/m ² per coat
Chemfit Top Seal 107	Waterproofing damp-proofing cementitious slurry; conforms to BBA Certificate No. 95/3174.	Waterproof and dampproof concrete, cementitious rendering, brickwork, block work.	25 kg set	2.0 kg/m ² per mm
Chemfit Elastic Seal 150	Two-pack elastic fiberreinforced, crack bridging, flexible waterproofing coating.	Protect concrete structures exposed to aggressive environment and flexural strains.	6.4 kg (A) + 20 kg (B) pack	1.7 kg/m ² per mm thickness

Resin Coatings

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit RC100	Epoxy floor coating.	Warehouses, floors.	20 kg kit	0.2 – 0.4 kg/m ²
Chemfit RC200	Self-leveling epoxy.	Industrial floors.	25 kg kit	1 – 3 mm thickness
Chemfit RC300	Polyurethane coating.	Outdoor surfaces.	20 kg kit	~0.3 kg/m ²
Chemfit Gard PW	Two-component, solvent free, non-toxic epoxy coating with outstanding mechanical and chemical properties.	Potable water tanks, pharmaceutical industries, concrete, wood, metal.	20 kg pail	3 – 4 m ² /kg
Chemfit Gard 63N	2-part epoxy protective coating for normal to highly aggressive chemical environment.	Concrete, cementitious mortars, epoxy mortars, steel, aluminum, food/beverage plants, sewage works, chemical plants.	10 kg unit	See PDS
Chemfit Elastic SG	Liquid applied, two component polyurethane resin based flexible membrane; conforms to ASTM C 836-95.	Exterior walls, basements, parking decks, roof decks, bathroom floors, plazas.	10 L, 20 L units	0.74 kg/m ² for 500 µm DFT

Liquid Applied Roofing Membranes

Product Name	Description	Uses	Packaging
Chemfit LiqMembrane 600	Elastic, one part polyurethane, highly crack bridging seamless liquid membrane.	Concrete, brickwork, asbestos cement, roof tiles.	7 kg, 21 kg containers
Chemfit RoofCoat 700	Flexible, liquid applied, single component acrylic based waterproofing and heat reflecting membrane.	GI Roofs, metal roofs, non trafficked areas.	18 kg plastic bucket
Chemfit PU601	PU base coat.	Roof systems.	20 kg
Chemfit PU620	PU UV topcoat.	Exposed roofs.	20 kg

Chemfit AC500 RoofGuard	Acrylic waterproof coating.	Roofs, non-traffic areas.	20 kg pail
Chemfit Raingard	Flexible, liquid applied, single component acrylic based ready-touse waterproofing and heat reflecting membrane.	Waterproof roofs, impervious coating on roofs, nontrafficked areas.	18 kg plastic bucket
Chemfit Lastic 621TC	High performance, cold applied, seamless, highly elastic liquid roof waterproofing top coat; conforms to ETAG-09/0139.	Waterproof exposed and builtup roofs in new construction and refurbishment.	15 L container
Chemfit Lastic 560	Cold-applied, one-component waterborne liquid applied membrane, highly elastic and UVresistant; conforms to ETAG-005 Part 8.	Roof waterproofing with many details and complex geometry.	5 kg, 10 kg, 20 kg pails
Chemfit Lastic 601-BC	High performance, cold applied, seamless, highly elastic liquid roof waterproofing base coat.	Waterproof roofs in new construction and refurbishment.	15 L container

6. Chemfit Flooring, Lining and Concrete Coating

Range Dry Shake Floor Hardeners

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit HardTop Quartz 1200	One part preblended colored mineral dry shake hardener comprising cement, quartz aggregates, admixtures, pigments; conforms to EN 206/1.	Warehouses, factories, shopping malls, public areas, restaurants, museums.	25 kg bag	5 kg/m ² (2.5-3 mm thickness)
Chemfit HardTop Metal 1210	Colored, one part metallic dry shake floor hardener containing hard metallic ferro silicon aggregates.	Heavy duty warehouses, transport terminals, power stations, distribution centers.	25 kg bag	7 kg/m ² (2.5-3 mm thickness)

Cementitious Flooring & Self-Leveling Screeds

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit Level G	One-component cementitious mortar for indoor flooring leveling and regularization.	Level holes, small and large surfaces, thickness 1-10 mm (10-30 mm with 30% 0-4 mm aggregates).	25 kg bag	Approx 2 kg/m ² per mm
Chemfit LevelFlow 1300	One part, polymer modified, pumpable selfsmoothing cementitious industrial screed; conforms to EN 13892-2.	Level precast concrete planks, industrial floors.	25 kg bag	1.77 kg/m ² per mm
Chemfit Level 100 T	One part, polymer modified, pumpable selfleveling fast hardening cementitious underlayment; conforms to EN 13892-2.	Provide suitable substrate for ceramic, stone, clay tiles, carpets, wood flooring.	25 kg bag	1.5 ± 0.1 kg/m ² per mm

Epoxy Primers

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit EpoxyPrime 1400	Two part epoxy primer, leveling mortar and mortar screed.	Primer for concrete, cement screeds, epoxy mortars	2.5 kg, 10 kg, 25 kg units	See PDS

Chemfit Floor 155WN	Solvent-free, water dispersed two part epoxy primer; conforms to DIN 52615.	Primer on new concrete, cementitious screeds, hardened concrete, existing epoxy coatings, EpoCem layers.	10 kg, 30 kg units	0.5 – 0.5 kg/m ² per coat (2-3.3 m ² /kg per coat)
Chemfit Floor 161	2-part epoxy primer, leveling mortar, intermediate layer and mortar screed.	Primer for concrete, cement screeds, epoxy mortars, flooring systems.	30 kg unit	See PDS

Epoxy-Cement Leveling Screeds

Product Name	Description	Uses	Packaging	Dosage/Yield/Coverage
Chemfit EpoCem 1700	Three part epoxy modified cementitious self-smoothing mortar (1.5-3 mm); conforms to EN 1504-9.	Temporary moisture barrier under epoxy, PU, PMMA floors over high moisture substrates, even green concrete	23 kg unit	2.25 kg/m ² per mm; min 4.5 kg/m ² for 2 mm
Chemfit EpoCem 82	Three part epoxy modified cementitious self-smoothing mortar (3-7 mm); conforms to EN 1504-9.	Temporary moisture barrier for thicker applications.	31 kg unit	2.25 kg/m ² per mm; min 6.75 kg/m ² for 3 mm

Epoxy Resin Floorings

Product Name	Description	Uses	Packaging
Chemfit EpoxySmooth 1500	Two part epoxy selfsmoothing and broadcast system; conforms to ISO 14644-1 Class 5.	Storage halls, workshops, garages, loading ramps.	20 kg unit
Chemfit Floor 2530W	Two part, water dispersed, solvent free, colored epoxy coating; conforms to DIN 4101-1 Class B1.	Epoxy coating for concrete, cement screeds, broadcast systems, epoxy mortar.	6 kg + 18 kg unit

Chemfit Floor 2430SG	Two part, water dispersed, solvent containing, colored epoxy coating.	Colored epoxy coating for medium to heavy mechanical & chemical exposure in production, workshops, warehouses, car parks.	20 kg unit
Chemfit Floor 261	2-part epoxy selfsmoothing, broadcast and textured coating, mortar screed and seal coat.	Concrete and cement screeds with normal to medium heavy wear: storage halls, workshops, garages, loading ramps.	20 kg + 10 kg unit
Chemfit Floor 263 SL	2-part epoxy selfsmoothing and broadcast system; conforms to ISO 14644-1 Class 5.	Storage halls, workshops, garages, loading ramps.	20 kg unit
Chemfit Floor 264	2-part epoxy roller and seal coat; conforms to ISO 14644-1 Class 4.	Roller coat for concrete, seal coat for broadcast systems in car parks, maintenance hangars, food industry.	30 kg unit

Polyurethane (PU) Floorings

Product Name	Description	Uses	Packaging
Chemfit PU Floor 1600	Two part PUR resin self-smoothing screed and seal coat; conforms to DIN 25415-1.	Food & beverage industry, wet working areas, normal to medium heavy mechanical & chemical stress.	25 kg unit
Chemfit PU Floor 350	Two-part, solvent free, highly elastic polyurethane resin for hot/tropical climates.	Highly elastic, crack bridging, trafficable, slip resistant wearing layers: car park decks, garage floors, bridges.	27 kg unit (A:9kg + B:18kg)
Chemfit PU Floor 358	2-part tough-flexible colored epoxy seal coat; conforms to EN 13501-1, DIN 51130 for class R11-R12.	Abrasion resistant flexible seal coat for industrial floors, car park decks, ramps, warehouses.	32.5 kg unit
Chemfit PU Floor 359	2-part PU tough-elastic colored seal coat; conforms to Rili-SIB 2001, DIN 51130.	Abrasion resistant flexible seal coat for industrial floors, car park decks, ramps, warehouses.	32.5 kg unit

High Chemical Resistance Floorings

Product Name	Description	Uses	Packaging
Chemfit ChemFloor 1800	Two part self-smoothing epoxy coating, highly chemically and mechanically resistant.	Bund areas, protection against water contaminating liquids.	25 kg pack
Chemfit Floor 381	2-part self-smoothing epoxy coating, highly chemically and mechanically resistant.	Chemically resistant coating for concrete and screed in bund areas.	25 kg pack
Chemfit Floor 390	2-part flexible and chemically resistant epoxy coating; conforms to Water Protection System Z-59.12107.	Crack-bridging chemically resistant coating for bund areas.	25 kg pack
Chemfit Asplit VEL	Vinylester resin based laminate conductive system; conforms to BGR 132.	Chemically stressed environments where high chemical resistance is mandatory.	See PDS

Hygiene Coatings (Antimicrobial)

Product Name	Description	Uses	Packaging
Chemfit HygGard 203W	Single component, waterborne modified acrylic resin coating containing antimicrobial proven to inhibit Staphylococcus aureus and E. coli (ISO 22196:2011).	Intermediate and surface coating for hygienic areas.	5 L, 15 L containers
Chemfit HygGard 205W	Single component waterborne modified acrylic resin coating with mid-sheen finish containing antimicrobial.	Surface coating for hygienic areas.	5 L, 15 L containers
Chemfit HygGard 215W	Single component waterborne modified acrylic resin coating with silver ion based antimicrobial.	Surface coating for hygienic areas requiring silver ion antimicrobial.	5 L, 15 L containers
Chemfit HygGard 307W	Single component waterborne acrylic/polyurethane dispersion coating with gloss finish containing antimicrobial.	Surface coating for hygienic areas requiring gloss finish.	5 L, 15 L containers
Chemfit HygGard 317W	Single component waterborne acrylic/polyurethane dispersion coating with silver ion antimicrobial.	Surface coating for hygienic areas with silver ion protection.	5 L, 15 L containers

Chemfit EpoxyHyg 183W CR	2-part water dispersed epoxy seal coat.	Epoxy coating for hygienic areas.	Part A: 10 kg, B: 6 kg
--------------------------	---	-----------------------------------	------------------------

7. Chemfit Sealing and Elastic Bonding Range

Primers & Backing Materials

Product Name	Description	Uses	Packaging
Chemfit Backing Rod	Extruded polyethylene based sealant back up material, available in various diameters.	Back up material for cold applied sealants to give correct thickness.	On demand
Chemfit Backing Filler	Extruded polyethylene closed-cell foam, joint filler available in boards and strips.	Back material for cold applied joints and joint filler.	On demand

Building Sealants

Product Name	Description	Uses	Packaging
Chemfit AcrylSeal 2000	One part plastic sealant based on acrylic dispersion, movement capacity 10%.	Indoor connection joints with low movement in concrete, aerated concrete, plaster, fiber cement, brick, wood, UPVC.	300 mL cartridge, 600 mL Unipack
Chemfit Silicone AC	One part acetoxy moisture curing silicone sealant.	Glazing and weatherproofing on non-porous substrates: glass, glazed ceramic tiles.	300 mL cartridge
Chemfit PolyFlex 2100	Polyurethane based, one part, moisture curing elastic joint sealant for outdoor applications; conforms to ISO 11600 F 25 HM.	Facade and floor joints in buildings and civil engineering constructions.	300 mL, 600 mL cartridge

High Temperature / Fire Protection Sealants

Product Name	Description	Uses	Packaging
Chemfit Silicone 3205C	Silicone weather seal for construction joints; conforms to ISO 11600, ASTM C920.	Seal, bond, mend in concrete applications, movement and connecting joints.	300 mL, 310 mL, 600 mL
Chemfit Firesil N	One part neutral curing, flame retardant silicone sealant; conforms to DIN 4102 B1, ISO 11600, ASTM C920.	Applications requiring flame retardance in construction and industrial areas.	300 mL cartridge

UV Resistant Elastic Coating

Product Name	Description	Uses	Packaging
Chemfit Floor N400 Elastic	One-part, highly elastic, solvent containing, UV resistant, colored, moisture curing polyurethane coating; complies to Z-59.12-4.	Concrete and cementitious screeds for balconies, terraces, footbridges, stairways, light to medium mechanical exposure.	6 kg, 18 kg units

8.Chemfit Corrosion Protection Range

Product Name	Description	Uses	Packaging	Dosage/Yield/ Coverage
Chemfit ZincRich 3200	Two component cold curing zinc rich epoxy primer, quick drying, weldable.	Anti-corrosive primer for iron, rebars, steel structures.	5 kg pack (A+B)	180 g/m ² for 25 µm DFT
Chemfit Permacor 2706EC	Two part, solvent based epoxy primer containing MIO; conforms to ENI 20000.	Protect galvanized steel, stainless steel, aluminum, zinc metal sprayed surfaces.	Part A: 20 k	

GET IN TOUCH WITH CHEMFIT

We are here to answer your questions, provide technical support, and help you select the right products for your construction projects. Whether you are a contractor, builder, engineer, or homeowner, our team is ready to assist you.

CONTACT INFORMATION

Head Office Address

Office No. 8, Near Gaey Soap
1 KM Sargodha Road
Faisalabad, Pakistan

Phone Numbers

0336-4544837
0324-1234999

Email Addresses

info@chemfitchemical.com

sales@chemfitchemical.com

customersupport@chemfitchemical.com

chemfit.pro@gmail.com

Website

www.chemfitchemical.com

Social Media

Facebook: Chemfit Construction Chemical
WhatsApp: +92 336 4544837
LinkedIn: Chemfit Chemical

Business Hours

Monday to Friday: 9:00 AM to 6:00 PM
Saturday: 10:00 AM to 2:00 PM
Sunday: Closed

Emergency Technical Support

For urgent technical support or on-site emergencies, we are available 24 hours a day, 7 days a week. Please call any of the phone numbers listed above.

GET A QUOTE

For inquiries, quotes, or technical support, please contact us via any of the methods above. Our team will respond within 24 hours.

You can also fill out the following information and send it to us via email or WhatsApp:

- Full Name:
 - Company Name:
 - Phone Number:
 - Email Address:
 - Product of Interest:
 - Estimated Quantity:
 - Project Location:
 - Any Specific Requirements:
-

FOLLOW US

Stay updated with our latest products, offers, and technical tips by following us on social media. We regularly post helpful content for construction professionals.

Facebook: Chemfit Construction Chemical

WhatsApp: +92 336 4544837

CHEMFIT CONSTRUCTION CHEMICAL AND SERVICES

Building Stronger | Creating Lasting Impressions

RELIABLE | INNOVATIVE | BUILD TO LAST

Thank you for choosing Chemfit. We look forward to working with you on your next construction project.